

E20-360

EMC

Network Storage - NAS Implementation

OfficialCerts.com is a reputable IT certification examination guide, study guides and audio exam provider. We ensure that you pass your E20-360 exam in first attempt and also get high scores to acquire EMC certification.

If you use OfficialCerts E20-360 Certification questions and answers, you will experience actual E20-360 exam questions/answers. We know exactly what is needed and have all the exam preparation material required to pass the exam. Our EMC exam prep covers over 95% of the questions and answers that may be appeared in your E20-360 exam. Every point from pass4sure E20-360 PDF, E20-360 review will help you take EMC E20-360 exam much easier and become EMC certified.

Here's what you can expect from the OfficialCerts EMC E20-360 course:

- * Up-to-Date EMC E20-360 questions as experienced in the real exam.*
- * 100% correct EMC E20-360 answers you simply can't find in other E20-360 courses.*
- * All of our tests are easy to download. Your file will be saved as a E20-360 PDF.*
- * EMC E20-360 brain dump free content featuring the real E20-360 test questions.*

EMC E20-360 certification exam is of core importance both in your Professional life and EMC certification path. With EMC certification you can get a good job easily in the market and get on your path for success. Professionals who passed EMC E20-360 exam training are an absolute favorite in the industry. You will pass EMC E20-360 certification test and career opportunities will be open for you.

<http://tripleamarine.com/?cert=exams.asp?examcode=E20-360>



Question: 1

Which layer in the OSI model does a router operate in?

- A. Data link
- B. Network
- C. Transport
- D. Application

Answer: B

Question: 2

Given this scenario, which statement is correct?

```
Server_mount server_2 -0 ro celdata /seldata
Server_export server_2 -p cifs -n celdatashare /seldata
\celdatashare (Everyone-Full Control)
\Engineering (Eng Group-R/W, Joe-Read)
\Sales (Sales Group-Read, Tim-R/W)
CELERRA.DOC (time-Read)
Sales Group - Time, Joe, Lisa
```

- A. Joe is granted R/W to the \Sales directory
- B. Ever one is granted Full Control to \Celdatashare
- C. Tim is granted R/W permission to the \Sales directory
- D. Everyone is granted Read only permission to \Celdatashare

Answer: D

Question: 3

You used Celerra's etherchannel trunking option to combine two 100 mb/sec. Ethernet ports into a single IP address and Mac address. What is the aggregate bandwidth that you can expect on the trunk?

- A. 100 mb/sec
- B. 125 mb/sec
- C. 150 mb/sec
- D. 200 mb/sec

Answer: A

Question: 4

Which NS600G/GS component is used to attach to an existing CX600?

- A. Internal Ethernet switch
- B. Serial Connection Assembly
- C. Direct attach to SPS-A and SPS-B
- D. Direct or SAN attached to SP-A and SP-B

Answer: D

Question: 5

Why does the Standby Power Supply (SPS) maintain power to the Storage Processors (SP) and the first [ist] Disk Enclosure (DAE2) during a power failure?

- A. To supply power to the Standby Data Mover

- B. To flush the write cache to disks 0-4 which houses the "Vault Area"
- C. To keep the first DAE2 and SPS running until power is restored
- D. To read the cache "Vault Area" regarding how to power down the NS600

Answer: B

Question: 6

The Celerra NS600 has a Disk Array Enclosures (DAE2) with fifteen disk devices. Which configuration is correct for DAE0, Bus 0, Enclosure 0?

- A. 4+1 RAID 5/Hot Spare/8+1 RAID 5.
- B. 4+1 RAID 5/RAID 1/Hot Spare/RAID 1/Hot Spare/RAID1
- C. 4+1 RAID 5/Hot Spare/4+1 RAID 5/4+1 RAID5/4+1 RAID 5/4+1 RAID 5
- D. 4+1 RAID 5/4+1 RAID 5/4+1 RAID 5/Hot Spare/RAID 0/Hot Spare/Hot Spare

Answer: A

Question: 7

On an NS600G/GS, the Celerra Control LUNs must be configured from a RAID 5 Group. Which RAID 5 group type and Disk drive type must they be?

- A. Any RAI Group on any DAE2, disks 0-4 ATA Disk
- B. A dedicated 4+1 RAID Group, on any DAE2, Fiber Disk
- C. Any RAID Group, on the 1st DAE2, and can be any drives in the enclosure Fiber disk
- D. Dedicated 4+1 RAID Group not necessary to be disks 0-4 on the first DAE2, ATA Disk

Answer: B

Question: 8

Each Disk Array Enclosure has a Loop ID and an Enclosure ID which are both set by the Enclosure Address Switch. WHAT IS THE enclosure ID an the Loop ID for the third Disk Array Enclosure?

- A. Loop ID = 0, Enclosure ID = 0
- B. Loop ID = 1, Enclosure ID = 0
- C. Loop ID = 0, Enclosure ID = 1
- D. Loop ID = 1, Enclosure ID = 1

Answer: C

Question: 9

To set up a Hyper Terminal connection to the Control Station, which settings are needed to configure Com 1 properties?

- A. 19200 bits per second, 7 data bits, parity, 1 stop bit, Hardware Flow
- B. 19600 bites per second, 8 data bits, no parity, 1 stop bit, Hardware Flow
- C. 19200 bits per second, no data bits, no parity, 1 stop bit, Hardware Flow
- D. 19200 bits per second, 8 data bits, no parity, 1 stop bit, Hardware Flow control

Answer: D

Question: 10

What does the Init Wizard configure on the Control Station?

- A. IP Address, Subnet Mask, Default Gateway

- B. IP Address, Subnet Mask, Broadcast Address
- C. IP Address, Subnet Mask, Default Gateway, Primary DNS server
- D. Domain Name, IP Address, Subnet Mask, Broadcast Address, Primary and Secondary DNS servers

Answer: A

Question: 11

What is required for an NS600G/GS to be connected to an existing CX600 via a Fiber Switch?

- A. One [1] or two [2] free ports per SP, five [5] unbound disk drives, Access Logix
- B. One [1] or two [2] free ports, 7+1 RAID five [5] Group with 6 LUNs, Access Logix
- C. One [1] or two [2] free ports per Fiber, five [5] unbound disk drives, PowerPath 3.01
- D. One [1] or two [2] free ports per Fiber Switch, five [5] unbound disk drives Access Logix

Answer: D

Question: 12

For Call Home to work at Company.com site, you must dial eight [8] to access an outside line. After changing to the /nas/sbin directory as root, which command should be issued to edit the dialing prefix number?

- A. ./ch_dd
- B. ./ch_cfg
- C. ./ch_stop
- D. ./ch_dialin_disable

Answer: A

Question: 13

Which additional hardware is required when converting an NS600G direct connect to Fabric connect?

- A. DAE2
- B. Switch
- C. Extra Data Mover
- D. Copper fiber cable

Answer: B

Question: 14

What is the environment of an NS600/NS600G with dual Data Movers configured as primary and standby?

- A. Low availability
- B. High Availability
- C. None critical data
- D. Mode two Operation

Answer: B

Question: 15

What are three components of an NS600 control station?

- A. Dual [2] GigE ports

OfficialCerts.com Certification Exam Full Version Features;

- Verified answers researched by industry experts.
- Exams **updated** on regular basis.
- Questions, Answers are downloadable in **PDF** format.
- **No authorization** code required to open exam.
- **Portable** anywhere.
- 100% success **Guarantee**.
- **Fast**, helpful support 24x7.

View list of All exams we offer;

<http://www.officialcerts.com/allexams.asp>

To contact our Support;

<http://www.officialcerts.com/support.asp>

View FAQs

<http://www.officialcerts.com/faq.asp>

Download All Exams Samples

<http://www.officialcerts.com/samples.asp>

To purchase Full Version and updated exam;

<http://www.officialcerts.com/allexams.asp>



Shop now using **PayPal**



3COM	CompTIA	Filemaker	IBM	LPI	OMG	Sun
ADOBE	ComputerAssociates	Fortinet	IISFA	McAfee	Oracle	Sybase
APC	CWNP	Foundry	Intel	McData	PMI	Symantec
Apple	DELL	Fujitsu	ISACA	Microsoft	Polycom	TeraData
BEA	ECCouncil	GuidanceSoftware	ISC2	Mile2	RedHat	TIA
BICSI	EMC	HDI	ISEB	NetworkAppliance	Sair	Tibco
CheckPoint	Enterasys	Hitachi	ISM	Network-General	SASInstitute	TruSecure
Cisco	ExamExpress	HP	Juniper	Nokia	SCP	Veritas
Citrix	Exin	Huawei	Legato	Nortel	See-Beyond	Vmware
CIW	ExtremeNetworks	Hyperion	Lotus	Novell	Google	

You have made the
Right Choice

You are becoming member of most comprehensive, accurate, highest quality and lowest cost certification resource in the world.

